# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications





# APC Back-UPS, 1600VA, Tower, 230V, 4 Universal outlets, AVR

BX1600MI-MS

### **Overview**

Load time	Harrathe in Otania
Lead time	Usually in Stock

### Main

Mairi		
Main Input Voltage	230 V	
Rated power in W	900 W	
Rated power in VA	1600 VA	
Product or component type	Uninterruptible power supply (UPS)	
output connection type	4 universal	
Cable length	1.2 m	
Number of cables	1	
Battery type	Lead-acid battery	
Range of product	Back-UPS	

### **Batteries & Runtime**

Run Time	View Runtime Graph ☐	
Efficiency	View Efficiency Graph ☐	
Number of battery filled slots	0	
Number of battery free slots	0	
Battery recharge time	8 h	
Battery voltage	24 V	
Battery life	35 year(s)	
Replacement battery	APCRBC176 ☐	
Battery graph comments	Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.	
Extended runtime	0	

### **General**

Provided equipment	user manual
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

### **Physical**

Colour	Black	
Height	19 cm	
Width	14 cm	
Depth	39 cm	
Net weight	10.3 kg	
Mounting preference	No preference	
Mounting mode	Not rack-mountable	
Two post mountable	0	
USB compatible	No	

# Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing	
Input voltage limits	140300 V	
Input Power Factor at Full Load	0.56	

## Output

Maximum configurable power in W	900 W	
Output frequency	50/60 Hz +/- 1 Hz sync to mains	
UPS type	Line interactive	
Wave type	Stepped approximation to a sinewave	
Full load runtime	00:01:00 900 W	
Half load runtime	00:06:30 450 W	
Maximum configurable power in VA	1600 VA	
Transfer time	6 ms typical : 10 ms maximum	

### Conformance

Product certifications	CE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

### **Environmental**

Ambient air temperature for operation	040 °C	
Relative humidity	095 % non-condensing	
Operating altitude	03000 m	
Ambient air temperature for storage	-1540 °C	
Storage Relative Humidity	095 % non-condensing	
Storage altitude	03000 m	
Acoustic level	40 dBA	
IP degree of protection	IP20	

# **Communications & Management**

### **Surge Protection and Filtering**

Surge energy rate 273 J

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.7 cm
Package 1 Width	49.5 cm
Package 1 Length	23.5 cm
Package 1 Weight	11.3 kg
SCC14	10731304410727

## **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability >

### ∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	Ec96232c-7000-4722-846e-a372cdfca8dc
REACh Regulation	REACh Declaration

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No